



0278-621 660

info@necks.se

Necks Electric AB

Tegelbruksvägen 22

821 43 Bollnäs

RAK LÄNK

Rak länk av stål.

LB nummer	A mm	D mm	Vikt kg	Tillåten kraft enligt SS kN	Korttidsström max kA-1s	E-nummer
4.39.2011	80	24	1,2	120	40	0624634
4.39.2063	110	24	1,4	120	40	-
4.39.2062	160	24	1,9	120	40	-
4.39.2071	180	24	2,1	120	40	-
4.39.2055	215	24	2,4	120	40	-
4.39.2054	240	24	2,7	120	40	-
4.39.2064	255	24	2,8	120	40	-
4.39.2075	285	24	3,1	120	40	-
4.39.2082	310	24	3,3	120	40	-
4.39.2072	355	24	3,7	120	40	-
4.39.2067	380	24	4,0	120	40	-
4.39.2058	390	24	4,1	120	40	-
4.39.2060	420	24	4,3	120	40	-
4.39.2061	470	24	4,8	120	40	-
4.39.2069	495	24	5,1	120	40	-
4.39.2083	510	24	5,2	120	40	-
4.39.2068	520	24	5,3	120	40	-
4.39.2070	600	24	6,0	120	40	-
4.39.2059	820	24	8,1	120	40	-
4.39.2073	1000	24	9,8	120	40	-
4.39.2087	1055	24	10,3	120	40	-
4.39.2056	1175	24	11,4	120	40	-
4.39.2074	1380	24	13,4	120	40	-
4.39.2049	1415	24	13,8	120	40	-
4.39.2048	1510	24	14,9	120	40	-
4.39.2057	1555	24	15,1	120	40	-
4.39.2065	1690	24	16,3	120	40	-
4.39.2066	1725	24	16,6	120	40	-
4.39.2076	1875	24	18,0	120	40	-
4.39.2077	1900	24	18,2	120	40	-
4.39.2079	2000	24	19,3	120	40	-
4.39.2078	2280	24	21,8	120	40	-
4.39.3101	140	35	3,2	240	40	-
4.39.3102	250	35	4,8	240	40	-
4.39.3103	345	35	6,1	240	40	-
4.39.3104	860	35	13,4	240	40	-
4.39.3107	1010	35	15,5	240	40	-
4.39.3108	1300	35	19,6	240	40	-
4.39.3105	1900	35	28,0	240	40	-
4.39.3106	2052	35	30,2	240	40	-